





Low Voltage Battery Datasheet

LB-5S-G1

LB-10S-G1

LB-15S-G1

LB-20S-G1

Description

The LB-(5-20)S-G1 series is a type of deep cycle and high capacity LFP battery with improved safety, long lifespan, and optimized user experience.

It is designed with an IP65 rating for more flexible and easier installation

It has superior performance with a capacity ranging from 5.12 kWh to 20.48 kWh for a single tower, which can meet residential electricity demand.

Features

01 LFP with improved safety design

05 Flexible capacity options from 5.12 kWh to 20.48 kWh

Stackable design without wiring

O2 Suitable for indoor/outdoor installation with IP65 design

06 Module level fire protection

Quick connector design saves installation time

Technical Specifications

Model	LB-5S-G1	LB-10S-G1	LB-15S-G1	LB-20S-G1
System Data				
Battery type	LiFePO4			
Rated capacity (Ah)	100	200	300	400
Number of modules	1	2	3	4
Total energy (kWh)	5.12	10.24	15.36	20.48
Rated voltage (V)	51.2			
Voltage range (V)	44.8-57.6			
Rated charging/discharging current	0.5C			
Max. continuous charging/discharging current (A)	50	100	150	150
Max. charge/discharge power (kW)	2.56	5.12	7.68	7.68
Communication	CAN, RS485			
Recommended depth of discharge (DOD)	90%			
Protection				
Overvoltage and undervoltage protection		Tratage		
Overcurrent protection	Integrate d			
Overtemperature and undertemperature protection				
DC breaker	d			
	Integrate			
General Dimensions (W × H × D [mm])(1)				
Weight (kg)(1)	665 × 503 × 200	665 × 770.7 × 200 Integ	665 × 1038.4 × 200	665 × 1306.1 × 200
Installation environment	61.5	109.5 d	157.5	205.5
Charging temperature (°C)	Indoor/Outdoor			
Discharging temperature (°C)	0 to +50			
Protection degree	-10 to +50			
_	IP65			
Cooling Altitude (m)	Natural convection			
Cycle life (25°C, 0.5C)	≤2000			
Certification	6000 Cycles, @90% DOD, 70% EOL			
	IEC 62619, UN 38.3			
Warranty		10 Y	'ears	

^{*}Parallel connection between battery towers is not supported.



