



# Microinverter Datasheet

**HMS-300-1T   HMS-350-1T   HMS-400-1T**  
**HMS-450-1T   HMS-500-1T**

## Description

With the output power up to 500 VA, Hoymiles new microinverter HMS-500-1T series rank among the highest for 1-in-1 microinverters.

All of these models listed are equipped with reactive power control and can meet the requirements of EN 50549-1:2019, VDE-AR-N 4105:2018, VFR2019, etc.

The new Sub-1G wireless solution enables more stable communication under various environmental conditions.

## Features

- 01 High-powered microinverter for 1-in-1 with output power up to 500 VA
- 02 With Reactive Power Control, compliant with EN 50549-1:2019, VDE-AR-N 4105:2018, VFR2019, etc.
- 03 Safer for rooftop solar stations with rapid shutdown compliance and isolated transformer

- 04 Connected to one panel, flexible for various applications
- 05 Sub-1G wireless solution allows stable communication with Hoymiles gateway DTU

# Technical Specifications

Model	HMS-300-1T	HMS-350-1T	HMS-400-1T	HMS-450-1T	HMS-500-1T
<b>Input Data (DC)</b>					
Commonly used module power (W)	240 to 405+	280 to 470+	320 to 540+	360 to 600+	400 to 670+
Maximum input voltage (V) MPPT	60	60	65	65	65
voltage range (V) Start-up voltage	16-60				
(V) Maximum input current (A)	22				
Maximum input short circuit current (A)	11.5	11.5	12.5	13.3	14
Number of MPPTs Number of	16	16	20	20	20
inputs per MPPT	1				
<b>Output Data (AC)</b>					
Rated output power (VA) Rated	1				
output current (A) Nominal					
output voltage/range (V)*	300	350	400	450	500
Nominal frequency/range (Hz)*	1.30	1.52	1.74	1.96	2.17
	230/180-275				
	50/45-55				
Adjustable Power factor (@nominal power)	> 0.99 default 0.8 leading ... 0.8 lagging				
Total harmonic distortion (@nominal power)	< 3%				
Maximum units per 10AWG branch**	24	21	18	16	14
Maximum units per 12AWG branch**	15	13	11	10	9
<b>Efficiency</b>					
CEC peak efficiency	96.7%	96.7%	96.7%	96.5%	96.5%
Nominal MPPT efficiency	99.8%				
Night power consumption (mW)	< 50				
<b>Mechanical Data</b>					
Ambient temperature range (°C)	-40 to +65				
Dimensions (W × H × D [mm])	182 × 164 × 30				
Weight (kg)	1.75				
Enclosure rating	Outdoor-IP67				
Cooling	Natural convection-No fans				
<b>Features</b>					
Communication	Sub-1G				
Type of isolation	Galvanically Isolated HF Transformer				
Monitoring	S-Miles Cloud (Hoymiles Monitoring Platform)				
Compliance	EN 50549-1: 2019, VDE-AR-N 4105: 2018, VFR2019, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3				

\* : Nominal voltage/frequency range can vary depending on local requirements.

\*\* : Refer to local requirements for exact number of microinverters per branch.



+91 9999055423 Manish Kaushik  
+91 9817900330 Neeraj Kumar



sunsolista@gmail.com  
www.sunsolista.com